

(12) **United States Patent**  
**Andrews et al.**

(10) **Patent No.:** **US 9,638,503 B1**  
(45) **Date of Patent:** **May 2, 2017**

(54) **DUAL SAFETY FUZE FOR GRENADE**

(71) Applicants: **William J. Andrews**, Tampa, FL (US);  
**Carl J. Campagnuolo**, Sarasota, FL (US)

(72) Inventors: **William J. Andrews**, Tampa, FL (US);  
**Carl J. Campagnuolo**, Sarasota, FL (US)

(73) Assignee: **The United States of America as Represented by the Secretary of the Army**, Washington, DC (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 442 days.

(21) Appl. No.: **14/462,702**

(22) Filed: **Aug. 19, 2014**

(51) **Int. Cl.**  
**F42C 15/20** (2006.01)  
**F42C 14/02** (2006.01)  
**F42C 15/00** (2006.01)  
**F42C 15/21** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F42C 15/005** (2013.01); **F42C 14/02** (2013.01); **F42C 15/21** (2013.01)

(58) **Field of Classification Search**  
CPC ..... F42C 14/02; F42C 14/025; F42C 15/005; F42C 15/20; F42C 15/21  
USPC ..... 102/482–488, 202.1  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,203,640 A \* 6/1940 Hines ..... F42C 14/02 102/261  
3,049,999 A \* 8/1962 Sunden ..... F42C 9/142 102/487

3,498,223 A \* 3/1970 Andersson ..... F42B 27/00 102/221  
3,731,631 A \* 5/1973 Berlin ..... F42C 14/02 102/487  
3,742,855 A \* 7/1973 Webb ..... F42C 14/02 102/261  
3,762,330 A \* 10/1973 Hall ..... F42C 14/02 102/487  
4,513,667 A \* 4/1985 Caruso ..... F42C 14/02 102/482  
H215 H \* 2/1987 Stewart ..... F42C 19/00 102/487  
4,926,752 A \* 5/1990 DiRubbio ..... F42C 14/02 102/202.13  
8,561,540 B1 \* 10/2013 Lauch ..... F42C 15/188 102/258  
8,857,341 B1 \* 10/2014 Andrews ..... F42C 14/02 102/486  
2006/0283346 A1 \* 12/2006 Luebbers ..... F42C 14/02 102/487  
2012/0145029 A1 \* 6/2012 Veksler ..... F42C 15/34 102/481

\* cited by examiner

*Primary Examiner* — Bret Hayes

(74) *Attorney, Agent, or Firm* — Michael C. Sachs

(57) **ABSTRACT**

A hand grenade fuze includes a secondary safety feature in the form of a trigger pin inserted through the striker lever. One end of the trigger pin has an undercut portion. A slide bar is disposed in the fuze body and has a keyhole opening at one end for selectively engaging the undercut portion of the trigger pin. A trigger has one end connected to the slide bar and another end rotatably fixed to the fuze body. A spring biases the trigger away from the fuze body. When the trigger is depressed, the slide bar translates and releases the trigger pin, which releases the restraint on the striker lever.

**8 Claims, 5 Drawing Sheets**

